



C12



T12



UB12B



DL12



UB12C



C12 FRP bench



DL12 bow step



DL12 niche for your feet



DL12 shower



DL12 under seat storage



DL12 ice box



UB12- Under deck fuel tank



UB12SC Seat and console

Technical specifications

Model	Overall Length	Overall Beam	Inside Length	Inside Beam	Air chambers	Tubes Ø	Weight	Max person	Max Load	Max HP/KW	Engine shaft	Lifting Points	Open Deck	Seat / Console	Fuel Tank	Water Tank / Shower	Rear Flat Seat	Rear Seat / Back Rest	Ice Box	Ladder	Bilge pump	Nav light	Bow Storage
C12	3,50mt	1,67mt	2,44mt	0,80mt	3	0,47	85 kg	5	658kg	26 KW	Short	4	X			X						X	
	11'6"	5'6"	8'	2'8"		19"	187lb		1450lb	35 HP	15"												
T12	3,50mt	1,67mt	2,44mt	0,80mt	3	0,47	95 kg	5	658kg	26 KW	Short	4		X			X					X	
	11'6"	5'6"	8'	2'8"		19"	210lb		1450lb	35 HP	15"												
DL12	3,70mt	1,77mt	2,48mt	1,00mt	3	0,44mt	171 kg	5	723kg	37 KW	Long	4		X	X	X		X	X	X	X		
	12'2"	5'9"	8'2"	3'3"		17'3"	378 lb		1593lb	50 HP	20"												
UB12B	3,63mt	1,67mt	2,76mt	0,94mt	3	0,44mt	160 kg	5	723kg	31 KW	Long	4	X		X		X					X	
	12'	5'6"	9'1"	3'11"		17'3"	352 lb		1593lb	40 HP	20"												
UB12SC	3,63mt	1,67mt	2,76mt	0,80mt	3	0,44mt	174 kg	5	723kg	31 KW	Long	4		X	X							X	
	12'	5'6"	9'1"	2'8"		17'3"	383 lb		1593lb	40 HP	20"												